WorkCentre 7655
shown with Advanced Finisher and Convenience Stapler options

WorkCentre 7665
shown with Professional Finisher and Convenience Stapler options

WorkCentre 7675
shown with High Capacity Feeder and Light Production Finisher with Folder option

	WorkCentre® 7655	WorkCentre® 7665	WorkCentre® 7675
OUTPUT SPEED – Printing and Copying			
Black and White	Up to 55 ipm (images per minute) A4/210 x 297 mm	Up to 65 ipm A4/210 x 297 mm	Up to 75 ipm A4/210 x 297 mm
Colour	Up to 40 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm
FIRST-IMAGE-OUT TIME – A4 Size, from Platen to Centre Tray			
Black and White	As fast as 5.5 seconds	As fast as 5.5 seconds	As fast as 5.5 seconds
Colour	As fast as 8.9 seconds	As fast as 8.9 seconds	As fast as 8.9 seconds

	Copy Specifications
COPYING	
Document Scanner	Duplex Automatic Document Handler (DADH) 250-sheet capacity
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution	Scan at 600 x 600 dpi, output at 2400 x 2400 dpi
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
Copy Pre-collation Memory (EPC)	512 MB DRAM 20 GB Disk minimum

Continued

Copy Specifications

COPYING (Continued)

Basic Copy Features & Options	Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fit selected paper size Hole Punching Booklet Creation Stapling Large Job Interrupt Copy on Tabs support Auto Paper Select Authentication for Services (i.e. Colour Copy) Auto Tray Switching
Imaging Copy Features	**Image Quality:** • **Original Type Selection**: Photo & Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps. • **Image Options:** Lighten/Darken, Sharpness, Saturation. • **Image Enhancement:** Auto Background Suppression, Auto and Manual Contrast. • **Colour Effects:** Off, Single Colour, Lively, Bright, Warm, Cool. • **Colour Balance:** Normal, Basic Colour, Advanced Colour. **Colour Shift:** • Superior Copy Image Quality Book Copying/Bound Copying Edge Erase (with Print to Edge option) Single Colour Repeat Image Mixed Size Original Image Shift (with Auto Centre option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates™ stamping (with colour capability)
Output Copy Features	Transparencies (blank or printed) Dividers (blank) Booklet Creation Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and recall job programming) Heavyweight paper (not rough stock)
Features	Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Xerox Standard Accounting (Copy, Print, Scan, Fax) Languages: (Select up to 20 languages for user interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian (Brazilian Portuguese), Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)

Continued

	Copy Specifications
COPYING (Continued)	
Security	IP Filtering for TCP/IP network communications Enable Secure Workflows Audit Log: Provide export capability of log, includes Username of log on attempts SNMPv3 Support LUI job queue Confidentiality: Require a PIN to delete a Secure print job Image Security Overwrite Auto On-demand Image Overwrite Encryption of user jobs stored on hard disk
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Size user-programmable percentages (100%, Auto%, 25%, 50%, 64%, 70%, 78%, 94%, 141%, 180%, 200%, 400%)
Foreign Device Interface (FDI) (Optional)	Interface to 3rd party access control devices, coin machines, card readers Validates Metadata Accept Authentication Login at LUI and pass to 3rd party Networking Account Interface with 3rd party accounting terminal for accounting UI MIB Compliance – supports the Finishing MIB Support a variety of vending stations available through the Xerox Custom Application Service
USB Port	PC Interface for upload/download of Internal Auditron data and Xerox Copier Assistant Customer device administration/software upgrade
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.
PAPER HANDLING - Duplex Automatic Document Handler	
Capacity	250 sheets
Speed	80 images per minute black and white, 50 ipm colour
Paper Sizes Sensed	A5/148 x 210 mm to A3/297 x 420 mm or A5/148 x 210 mm to A4/210 x 297 mm
Weights	80 gsm to 105 gsm

Copy Specifications

PAPER HANDLING - Four Front Loading Paper Trays - Paper Trays 1,2,3 & 4

Capacity	
(trays 1 & 2)	500 sheets of 90 gsm each tray
(tray 3)	870 sheets of 90 gsm
(tray 4)	1,140 sheets of 90 gsm
Sizes	
(trays 1 & 2)	A5/148 x 210 mm to A3/297 x 420 mm
(trays 3 & 4)	A4/210 x 297 mm
Weights	64 gsm to 220 gsm
Types	Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Custom

PAPER HANDLING - Bypass Tray

Capacity	250 sheets of 90 gsm
Sizes	101.6 x 152.4 mm SEF, SRA3 SEF, B5 SEF, A4 SEF & LEF, B4 SEF, A3 SEF
Weights	64 to 300 gsm
Types	Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Custom

PAPER HANDLING - High Capacity Feeder (HCF)

Capacity	2000 sheets of 90 gsm
Sizes	210 x 297 mm / A4 LEF, 184 x 266.7 mm LEF
Weights	64 to 220 gsm

PAPER HANDLING - Total Capacity

Device Total Capacity	5,260 sheets

Copy Specifications

OUTPUT OPTION - Simple Catch Tray (SCT) Option	
Capacity	500 sheets of 90 gsm
OUTPUT OPTION - Offsetting Catch Tray (OCT) Option	
Capacity	500 sheets of 90 gsm
OUTPUT OPTION - Advanced Office Finisher	
Capacity	**Top tray:** 500 sheets **Lower tray:** 3,000 sheets of 90 gsm, A4/210 x 297 mm
Sizes	101.6 x 152.4 mm to 304.8 x 482.6 mm
Weights	64 to 300 gsm
Stapling	50 sheets of 90 gsm
Hole Punch	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
OUTPUT OPTION - Professional Finisher (with Booklet Maker)	
Capacity	**Top tray:** 500 sheets **Lower tray:** 1,500 sheets of 75 gsm, A4/210 x 297 mm
Sizes	101.6 x 152.4 mm to 304.8 x 482.6 mm
Weights	64 to 300 gsm
Stapling	50 sheets of 90 gsm
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheets maximum)
OUTPUT OPTION - Convenience Stapler	
Capacity	5,000 staples Requires a separate outlet
OUTPUT OPTION - Light Production Finisher	
Capacity	**Top tray:** 500 sheets **Lower tray:** 2,000 sheets of 80 gsm, A4/210 x 297 mm
Sizes	101.6 x 152.4 mm to 304.8 x 482.6 mm
Weights	64 to 300 gsm
Stapling	Up to 100 sheets of 80 gsm

Continued

Print Specifications

OUTPUT OPTION - Light Production Finisher (Continued)	
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheets maximum)
Post Process Interposer	200 sheet capacity
OUTPUT OPTION - Light Production Finisher with Folder	
Capacity	**Top tray:** 500 sheets **Lower tray:** 2,000 sheets of 80 gsm, A4/210 x 297 mm
Sizes	101.6 x 152.4 mm to 304.8 x 482.6 mm
Weights	64 to 300 gsm
Stapling	Up to 100 sheets of 80 gsm
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheets maximum)
Post Process Interposer	200 sheet capacity
Folding	Single Sheet C- and Z-folding on 60 to 90 gsm, A4 / A3-sizes **Folding Tray:** Up to 40 sheets
NETWORK PRINTING - SMart Controller (Simultaneous rip, receive, programme ahead, queue processing, and transmit)	
Processor	1.8 GHz Athlon
Memory (ESS)	1 GB
System Disk	80 GB
Print Languages (PDL)	PCL 6 / PCL 5e emulation PostScript 3 emulation TIFF (6.0 Old JPEG and New JPEG) TIFF Fax Extended (TIFF - FX) PDF LCDS, SCS, XES and IPDS through 3rd-party transforms
NETWORK PRINTING - Resolution (printing via CentreWare® software)	
	PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey) PCL: 600 x 600 dpi Supports PCL and PS switching within job

Print Specifications

NETWORK PRINTING - Printing Features

Bi-directional Print Drivers provide device and job status
Embedded Web server for remote control/monitor/setup
Job monitoring at the device and at desktop
Special font
Banner Sheet
Rotate Image
Offset
Support PCL and PS switching
Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print)
Support for Print on Tabs / Page Segmentation
Linearized PDF
Save and restore print job settings

NETWORK PRINTING - Print Driver Options

Paper Output

Job Type
- Secure, Sample, Delay

Paper Selection by attribute (including transparency separators)
Duplex (2-sided)
Finishing
- Multiple stapling positions
- Hole punch
- Booklet creation
- Fit to new paper size
- Saddle stitch with Professional Finisher and Light Production Finishers

Output tray selections
Store and recall driver setting

Special Pages

Exception page programming (covers, inserts/tabs, exception pages)

Image Options

Light/Dark
Toner saver
Resolution options (600 x 600 and 1200 x 1200 dpi)
Reduction/Enlargement
Margins (edge to edge printing)
Invert Image (negative/mirror)

Layout/Watermark

N-up (16) / Multi-up
Booklet Layout/Finishing
Fit to new paper size
Image orientation
Watermark option

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 10/100BaseT, 10BaseT, 10Base2 (IEEE802.5) (Token ring) – via adapter, wireless Ethernet (IEEE802.11a/b/g) - via 3rd party adapter
USB 2.0 / IEEE1284 Parallel Port Kit option
IPv6 support for printing
802.1x support

Continued

Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

Operating Systems	Microsoft Windows 2000, XP, Windows Server 2003, Windows Vista, Citrix, Novell NetWare 4.x, 5.x, 6 Mac OS 8.x, 9.x, OS X, 10.3 and higher Solaris 2.8, 2.9, 2.10 HPUX 11.0, 11iv2 AIX 5l v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4
Network Protocols	TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX, IPP, NDPS®/NEPS AppleTalk/EtherTalk, Bonjour
Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet
Security Protocols/Features	**Protocols:** • HTTPS • IPsec **Features:** • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Hide print job in queue • Hard drive encryption • Auto On-demand Image Overwrite • Xerox Secure Access option
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (TrueType fonts) PostScript 3: 136 PostScript standard fonts (TrueType fonts/send fonts as/substitution table)

Print Drivers

Environment	***PCL XL/5C***	***PostScript 3***
Windows 2000/XP, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit)	Bi-directional enhanced (Xerox custom graphical user interface)	Bi-directional enhanced (Xerox custom graphical user interface)
Macintosh System 8.x - 10.2	N/A	Generic PPD Bi-directional via AppleTalk (9.x)
Macintosh System 10.3 and higher	N/A	Bidirectional enhanced (Xerox custom graphical user interface)

Print Submission Tools

Environment	***PCL***	***PostScript 3***
Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5l v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4	Submission Tool only	Submission Tool with full feature set (Includes administration, GUI/TTY print driver and software installation)
TIFF/PDF: Supported in Windows 2000/XP, Windows Server 2003, Windows Vista	Submission Tool for any TIFF or PDF file	N/A

	Print Specifications
DEVICE MANAGEMENT	
	Font Management Utility for downloading additional fonts (available for Windows and Mac)
Software Installation and Upgrade	Network Controller Install Wizard Software Upgrade via Network
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
E-Services	Automated Billing Meter Reads
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device.
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS	Server gateway application: centralised management tool
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli Netware	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (Optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

Continued

Print Specifications

DEVICE MANAGEMENT (Continued)

Xerox Device Types for SAP R/3 Environment Available at ***www.xeroxofficesapsolutions.com***	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): • One- to two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and colour – provide ability to select different paper types and paper colours, such as transparency, red, etc. • Print security via PIN ID capability • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.

CENTREWARE INTERNET SERVICES - Integrated Web Pages Provided by the Device

Device Status	Web server embedded on SMart Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files PS, PCL, TIFF, PDF Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	Supports 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers (minimum versions)	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x
Support	Online support available via web page

SCANNING

Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs.

Continued

	Print Specifications
SCANNING (Continued)	
Input Speed	Scan at up to 50 ipm colour scanning, up to 80 ipm black and white – A4/210 x 297 mm at all resolutions
Resolutions (DPI Options)	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	Archival Record (Normal Quality - Smallest file size) For Sharing and Printing (Normal Quality - Small file size) For High Quality Printing (High Quality - Large file size) For OCR (High Quality - Large file size) Simple Scan (Normal Quality - Small file size)
Quality / File Size	Normal Quality (Small file size) Higher Quality (Large file size) Maximum Quality (Largest file size)
Maximum Scan Area	A3/297 x 420 mm
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x / 5.x / 6.x) PIN-based guest login
File Formats	TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages) PDF (image only and searchable PDFs with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression) JIFF with JPEG compression Microsoft XML Paper Spec (XPS)
Scan Features	Mixed sized Original Support for Scan Export New scan to export compression formats: • MRC (multi-layer) • JBIG2 Simplify the scanning workflow User Interface (IQ, file size, Templates) Enhanced IQ Support for Barcode Readers and OCR Scan in Novell IP Build job for Scan to File Auto Detect Colour or Black and White Image data Auto Contrast support for Scan Export – Enable better colour and greyscale scanned Image Quality by correcting for different levels of black within a scanned image Scan to Searchable PDF, PDF/A and XPS Scan to Home Scan to Mailbox Store and reprint print jobs

	Print Specifications
SCAN TO EMAIL - Optional	
Capability	Scan to email (manual address entry), directory (Exchange/Notes/LDAP) address searching, internal address book or Public address book (up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options
NETWORK SCANNING - Optional	
Capability	Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services: • Scan to file • Scan to network server / directory • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com • Scan to email • Scan to Microsoft Exchange public folders • Scan to PC Desktop
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP / IP HTTP / HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: Fields (Metadata) • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations • Customised fields viewed on user interface • Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job (for scan to file only) (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge
NETWORK SCANNING - Software Solutions	
Supported Scan Destinations - scan template creation (Varies by scanning software options purchased)	Scan to application (workflow, Electronic Document Management System / Repositories) Scan to Microsoft Exchange 2000 Web folders Scan to Web URL Scan to remote printer Scan to PC Desktop (SE and Professional editions) Scan to Mailbox

Continued

Copy Specifications

NETWORK SCANNING - Software Solutions (Continued)

FreeFlow Scan to PC	A desktop offering that provides document imaging, archiving, editing and organisation tools:
Desktop SE (optional)	• ScanSoft PaperPort SE 10 – image viewing and file management software • ScanSoft OmniPage SE 3.0 – offer desktop / client installation – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops

FreeFlow Scan to PC Desktop Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:
	• ScanSoft PaperPort Professional 10 image viewing and file management software:
	  • Complete PDF functionality
	  • Secure PDF workflow of all scanning applications
	• ScanSoft OmniPage Pro 14 Office (for desktop / client installation) – Professional OCR software for digital archiving and document conversion
	• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability

FreeFlow SMARTsend (optional)	Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): • Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery • Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to File Destinations: email, Novell Netware folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint • Workflow initiation via device scanning user interface (template selection at device UI)
FreeFlow SMARTsend Professional (optional)	Everything in Free Flow SMARTsend, plus: • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Adding of Metadata information • Scan to Internet fax file destination

Fax Specifications

FAX OPTIONS - Walk Up Option (one or two lines options)

Compatibility	ITU (CCITT) Group 3
Memory	32 MB (One line) 256 MB (Two line)
Speed / Modems	1 or 2 V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time.
Compression / Speed	MH / MR / MMR / G3 / Super G3

Continued

Fax Specifications

FAX OPTIONS - Walk Up Option (one or two lines options) (Continued)

Fax Send Features	Quality / Resolution • Original type: Photo, Photo/Text, Text Only • Fax – off Platen, mixed sizes or Bound / Book Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce / Split large documents Cover letter Delayed send Build Job (up to 1,000 images) Polling
Fax Receive Features	One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header) / Auto Auto answer delay Secure receive Junk fax prevention
Fax Reports	Activity Dial directory Group directory Options Pending Jobs
Fax Mailboxes	Up to 200 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	**Speed Dials:** • 200 (One-line option) • 1,000 (Two-line option) Group Dials: • Up to 100 groups with up to 200 recipients per group (One-line option) • Up to 200 groups with up to 400 recipients per group (Two-line option) Auto Redial: • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)

Fax Specifications

FAX OPTIONS - Walk Up Option (one or two lines options) (Continued)	
Resolutions	***Send:*** 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 600 x 600 dpi (Superfine) ***Receive:*** 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Superfine) 400 x 400 dpi (Superfine) 600 x 600 dpi (Superfine)
LAN Fax	Send fax directly from print drivers
FAX OPTIONS - Internet Fax	
Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	A3/ 297 x 420 mm
Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)

Continued

Fax Specifications

FAX OPTIONS - Internet Fax (Continued)	
Compliance	ITU-T T.37 complaint 508 Compliant
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation: • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body
FAX OPTIONS - Network Fax Server Enablement	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.
Maximum Scan Size	A3/ 297 x 420mm
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login
Network Protocols	Novell (NCP via IPX / SPX) or IP FTP Microsoft SMB via TCP / IP HTTP / HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to A3/ 297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, five levels of contrast, five levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com

Fax Specifications

ACCOUNTING OPTIONS - Internal Auditron

Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Auditron report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software

ACCOUNTING OPTIONS - Xerox Standard Accounting

Tracking	Copy, Print, Fax and Scan usage to secure print
Accounting	Up to 2,500 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the Web UI or the device GUI in tools, admin can manage the feature remotely via the Web UI, Data can be exported via a CSV file, supports entering XSA ID into the print driver when submitting a print job.

ACCOUNTING OPTIONS - Job Based Accounting - 3rd-Party enablement

Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts

Machine Specifications

MONTHLY DUTY CYCLE

WorkCentre 7655: up to 200,000 pages/month
WorkCentre 7665: 300,000 pages/month
WorkCentre 7675: 300,000 pages/month

Average Monthly Print Volume*	15,000 to 50,000 pages per month

ELECTRICAL REQUIREMENTS

Voltage : 220-240 VAC +/- 10% (198-264 VAC)
Frequency: 50/60 Hz +/- 3%, 10 A (220/240 V)
Power Consumption: 1.145 KVA maximum printing continuously

** Average monthly print volume - expected regular monthly print throughput.*

Machine Specifications

POWER CONSUMPTION	
Running	< 1104 watts/hour
Standby	< 285 watts/hour
Low Power Mode	< 218 watts/hour (Default time to Low Power = 15 minutes)
Auto Off / Sleep mode	< 23.7 watts/hour (Default time to Sleep mode = 45 minutes)
Warm-up Ready to Copy	< 28 seconds (Recovery from Sleep)
Warm-up Ready to Print	< 130 seconds (Recovery from Sleep)
Low Power Recovery	< 20 seconds

ENVIRONMENTAL CONSIDERATIONS	
Required Temperature Range	10° to 28° C
Required Relative Humidity	10% to 85%

DIMENSIONS AND WEIGHT	*width*	*depth*	*height*	*weight*
Configuration with SCT or OCT	1,574 mm	921 mm	1,460 mm	277.7 kg
With Advanced Office Finisher	2,096 mm	921 mm	1,460 mm	351.7 kg
With Professional Finisher (with Booklet Maker)	2,096 mm	921 mm	1,460 mm	379.4 kg
With Light Production Finisher	2,286 mm	921 mm	1,460 mm	398.2 kg
With Light Production Finisher with Folder	2,489 mm	921 mm	1,460 mm	455.9 kg

CERTIFICATIONS	
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 73/23/EEC (Europe) 95/5/EEC (Europe) Energy Star

Device Specifications

XEROX EXTENSIBLE INTERFACE PLATFORM (EIP)

Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customised user interfaces, and card-based authentication solutions supporting a personalised user experience.

SUPPLIES	*Description*	*Order Number*
Toner Cartridges	Black	006R01223
	Cyan	006R01226
	Magenta	006R01225
	Yellow	006R01224
Waste Toner Bottle	Supplied with each toner cartridge box	008R12990
Staple Cartridge	For Office Finisher / Advanced Office Finisher	008R12964
Staple Cartridge	For Light Production Finisher	008R13029
Staple Cartridge	For Booklet maker saddle-stitch stapling	008R12925
Staple Cartridge	For Convenience Stapler • Complete Cartridge • Refill Cartridge	 008R12964 008R12941

SMART KITS	*Description*	*Order Number*
Fuser Module	Includes ozone filter	008R12989

© 2008 Xerox Corporation. All rights reserved. XEROX®, WorkCentre®, CentreWare® and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency (does not include WorkCentre 7655 copier version). Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Product information and/or specifications are subject to change without notice.
11/08 W65SS-01EH